

КАТАЛОГ ТОВАРОВ

Гайки Т-образные
для алюминиевого
станочного профиля



T Nut




Application: Subsequent nut for aluminum profile

Features: Can be directly put into the aluminum trough and then rotated 90 degrees for fastening, with high connection strength, strong versatility and easy installation

Material: Galvanized Carbon Steel




Slot Width 6mm-20 Series




Application	Order No.	D	Weight(g)
20 Series	TM6-4	M4	1
	TM6-5	M5	1

Slot Width 8mm-30 Series




Application	Order No.	D	Weight(g)
30 Series	TM8-4-30	M4	4
	TM8-5-30	M5	4
	TM8-6-30	M6	4

Slot Width 8mm-40 Series



Application	Order No.	D	Weight(g)
40 Series center hole-φ6.8	TM8-4-40	M4	6
	TM8-5-40	M5	6
	TM8-6-40	M6	6

Slot Width 10mm Series



Application	Order No.	D	Weight(g)
40 Series center hole-φ12 45、50、60 Series	TM10-4	M4	8
	TM10-5	M5	8
	TM10-6	M6	8
	TM10-8	M8	7

Roll In T-nut




Application: Subsequent nut for aluminum profiles

Features: Roll in T-nut is the neglected nut, which can locate any point

Material: Galvanized Carbon Steel




Slot Width 6mm-20 Series




Application	Order No.	D	Weight(g)
20 Series	TH6-4	M4	2.1
	TH6-5	M5	1.9

Slot Width 8mm-30 Series



Application	Order No.	D	Weight(g)
30 Series	TH8-4-30	M4	7
	TH8-5-30	M5	6.6
	TH8-6-30	M6	6.2
	TH8-8-30	M8	5.8

Slot Width 8mm-40 Series



Application	Order No.	D	Weight(g)
40 Series center hole- $\phi 6.8$ (except light type)	TH8-4-40	M4	11
	TH8-5-40	M5	11.3
	TH8-6-40	M6	11.7
	TH8-8-40	M8	8.8



8 (800) 555-63-74 бесплатные звонки по РФ
+7 (473) 204-51-56 Воронеж
+7 (495) 505-63-74 Москва



www.purelogic.ru
info@purelogic.ru
394033, Россия, г. Воронеж,
Ленинский пр-т, 160, офис 149

Пн	Вт	Ср	Чт	Пт	Сб	Вс
	8 ⁰⁰ -17 ⁰⁰			8 ⁰⁰ -16 ⁰⁰		выходной